



ENVIROMAT® 20MM DRAINAGE BOARD

■ **PRODUCT ORDER CODE** ENV-DRAINAGE BOARD

■ **STANDARD SIZE** 0.97m x 50m Rolls (48.5m²)

Thickness: 21mm

Approximate weight: 1.2kg/m²

This product is supplied by the square metre cut to size. All measurements are approximate.

■ **PERFORMANCE** Water storage capacity: 4 l/m²

Water Flow: 24 l/m²/s

■ **DETAILS**

A 20mm Black HDPE (high-density polyethylene) punched cusplate drainage board with a geotextile filter fleece bonded to a single side (top). The 20mm cusplate provides water storage of up to 4 litres per square metre with 10mm diameter punched perforations, ensuring an overflow performance of 24 l/m²/s. The attached filter fleece stops small particles from washing into drains without hindering water permeability.

■ **USES**

Provides an irrigation and drainage system for greenroofs.

**A TOUGH CUSPATE
DRAINAGE BOARD WITH
INTEGRAL FILTER FLEECE,
IDEAL FOR INTENSIVE
AND SEMI-INTENSIVE
GREENROOFS.**

FEATURES

Optimised for maximum strength and performance.

UV stabilised.

High crush and puncture resistance.

High flow rate.

Easy to cut..

Important - Although this product has been UV stabilised it is advisable to store it out of direct sunlight until it is used.

