



## Stain Protect Pro Invisible Stain Protection

### Product Summary

A water based impregnator providing modular pavements with protection from dirt, grease and oil stains.

### Product Applications

Designed for use on all types of exterior and interior paving units.

### Product Description

A professional surface impregnator for natural stone, porcelain, clay and precast concrete paving. Providing invisible and vapour permeable protection against staining by oil, fat and grime.

Paving is easier to clean, reducing long-term maintenance costs.

Treated paving has no change to colour, texture or slip resistance.

Stain Protect Pro is resin, polymer and solvent free.

### Directions for Use

Wear suitable protective clothing and test an inconspicuous area.

Do not dilute. Apply when the surface is between  $\geq 10^{\circ}\text{C}$ .

1. Ensure the surface to be treated is clean and dry
2. Apply Stain Protect Pro using a brush, sponge or roller, removing excess liquid as work proceeds.
3. Allow to dry uniformly for at least two hours before walking on.

Apply 1-2 coats max. depending on paving unit porosity.

Full protection develops within 2-4 days.

If pre-treating paving units before installation, avoid coating the sides and base with Stain Protect Pro.

### Storage Life

**Storage life:** at least 12 months stored in original container in frost free conditions.

## Technical Specification

|   |  |
|---|--|
| <b>Usage</b>  | Invisible Stain Protection   |
| <b>Characteristics</b>  | Water Based Impregnator  |
| <b>Colour</b>   | Clear  |
| <b>Packaging</b>  | 1L Bottle, 5L or 10L Canisters                                       |
| <b>Weight</b>   | 1, 5 or 10 kg  |
| <b>Dilution (with water)</b>  | Do not dilute  |
| <b>Typical consumption / coverage</b>   | 1 L bottle: 10 - 20 m <sup>2</sup><br>(Depending on paving porosity) |
| <b>Containers per box</b><br><i>(can be shipped together with other weISS products)</i> | 1L: 12<br>5L: 4<br>10L: singular                                     |
| <b>Box weight</b>   | 12 - 20 kg   |
| <b>Working temperature</b>  | $\geq 10^{\circ}\text{C}$  |
| <b>Protection Duration</b>  | $\geq 12$ months   |
| <b>Warning / Danger statements</b>  | Wear suitable PPE  |
| <b>Storage life</b>   | $\geq 12$ months from manufacture date                               |



**Steintec**<sup>®</sup>  
high performance paving mortars

1 Northwick Rd  
Canvey Island  
Essex  
SS8 0PU  
**+44 203 598 9800**  
www.steintec.co.uk