

Flush floor covers featuring a recessed centre plate designed to accept carpet or vinyl flooring for a concealed finish.

- Recess mounted aluminium floor joint covers featuring two TPR gaskets to accommodate larger movement
- Centre plate is recessed to accept floor finishes up to 3.2mm thick
- Easy to clean; ideal for interiors where hygiene is important
- Suitable for areas where light wheeled equipment is in use
- GTR(W) models require a consistent joint width
- DGTR(W) models can be fitted over a range of joint widths
- Gaskets are replaceable on-site
- Load capability: 250kg point load



FLOOR FINISH | Up to 3.2mm thick | Carpet | Vinyl

FLOOR TO FLOOR COVERS


Model	Joint width range (mm)	Frame depth (mm)	Exposed surface (mm)	Min. recess required (mm)		Movement (mm)		
				Depth*	Width	↔	↕	↗↘
DGTR-200	35-58	30	165	35	175	±20	±8	±6
DGTR-300	53-85	30	254	35	264	±38	±12	±8
DGTR-400	53-110	30	279	35	289	±38	±15	±8
GTR-200	50	16	165	21	175	±20	±8	±6
GTR-300	75	16	254	21	264	±38	±12	±8
GTR-400	100	16	279	21	289	±38	±15	±8

\* From FFL

FLOOR TO WALL COVERS

Model	Joint width range (mm)	Frame depth (mm)	Exposed surface (mm)	Min. recess required (mm)		Movement (mm)		
				Depth*	Width	↔	↕	↗↘
DGTRW-200	10-54	30	108	35	113	±10	±2	±3
DGTRW-300	20-80	30	164	35	169	±19	±3	±4
DGTRW-400	20-105	30	189	35	194	±19	±5	±4
GTRW-200	50	16	108	21	113	±10	±2	±3
GTRW-300	75	16	164	21	169	±19	±3	±4
GTRW-400	100	16	189	21	194	±19	±5	±4


DGTR-200



Recessed centre plate takes up to 3.2mm thick floor finish for maximum concealment.


Deep frame models offer installation flexibility, as they can be installed over joints with varying widths. DGTR-200 for example can be fitted over joints from 35 to 58mm wide, whilst maintaining the same movement capability.

GTR-200




Shallow frame models require a consistent joint width along their length.

DGTRW-200



Wall frames are natural anodised as standard.

GTRW-200



Our TPR gaskets are smooth, strong and offer a hygienic seal.

MATERIALS, COLOURS AND FINISHES

- **Aluminium sections:** mill finished as standard, except for wall frames which are supplied in a natural anodised finish.
- **Gaskets:** co-extruded Thermoplastic Rubber (TPR) gaskets are available in four standard colours. Other colours can be supplied subject to minimum quantity.



COMPLEMENTARY WALL/CEILING COVERS

GTW Series ▶ 53

For more information visit:  
[www.c-sgroup.co.uk/3985](http://www.c-sgroup.co.uk/3985)

ACCESSORIES

- Fire Barriers ▶ 90-91
- Moisture Barriers ▶ 92
- Acoustic Barriers ▶ 93

STOCK LENGTHS

- **Aluminium sections:** 3m
- **Gaskets:** supplied cut to suit from [max] 32m rolls

FIXINGS

- **Floor:** fixings (by others) to suit substrate at 450mm centres and to achieve minimum 40mm embedment
- **Wall:** fixings (by others) to suit substrate at 450mm centres

NB: Frames are supplied undrilled.